

# ViewSonic® CDE WIRELESS PRESENTATION DISPLAYS

## AVAILABLE SIZES

RE-AV55VSD 55" | W1243.2 H714 D74.8

RE-AV65VSD 65" | W1450.6 H828.1 D78.5

RE-AV75VSD 75" | W1672.0 H955.0 D70.0

## PRODUCT DESCRIPTION

The ViewSonic CDE6520 is a commercial display with a slim even bezel, offering the combination of cost-efficiency and ease of installation for corporate, retail and hospitality environments. Integrated with an embedded media player, the CDE6520 is able to easily playback high definition messaging via USB port. Versatile connectivity options include 2 HDMI-IN ports, RS232 input, SPDIF output etc. The slim-bezel CDE6520 delivers sharp and vivid images to ensure crisp pictures and smooth content playback.



# ViewSonic® CDE WIREFLESS PRESENTATION DISPLAYS

---

## KEY FEATURES

- Display: Panel Size: 65 / Type/ Tech: TFT LCD Module. IPS type, DLED backlight / Display Area (mm): 1428.48(H) – 803.52(V) (65 diagonal) / Native Resolution: 16:09 / Aspect Ratio: 3840 x 2160 / Colors: 1.07B colors / Brightness: 350 nits (typ.) / Contrast / Ratio: 1200:1 Typ. / Response Time: 6 ms / Viewing Angles: H = 178, V = 178 typ. / Backlight Life: 30,000 Hours Min Typ / Surface Treatment: Anti-Glare, 2H, Haze 3% / Bezel: Slim / Orientation: Landscape
- INPUT: HDMI: x2 / DVI: x1 / Audio: x1 (3.5mm) / RS-232: x1 / IR Pass Thru: x1
- OUTPUT: Audio: x1 (RCA) / SPDIF: x1 (Fiber) / IR Pass Thru: x1
- LAN: RJ45: x1
- USB: Type A: 2.0 Type A : x2 (USB Playback)
- SPEAKERS: 10Wx2
- COMPATIBILITY: RGB PC/HDMI PC: Up to 1920×1080@60Hz / HDMI: 480i, 480p,720p,1080i,1080p, 4K2K@60Hz / DVI: 480i, 480p,720p,1080i,1080p / Android Version: Android 8.0
- POWER: Voltage: 100-240 VAC +/- 10% Wide Range / Consumption: Normal 70 W, Max 85w
- ERGONOMICS: Wall Mount (VESA ): 400×200 mm
- PACKAGE CONTENTS: 1. CDE4320 commercial display. Remote Control with batteries4. Quick Start Guide5. Power Cables (1.8mm)6. HDMI cable (1.8mm)7. RS232 cable (1.8m)